

Hartmann & König
STROMZUFÜHRUNGS AG



Spring cable reels on demand


In 48 hours ready for dispatch - now with accessories

- 48-hour spring cable reels now available with accessories (ratchet, roller yoke, cable grip)
- in well-known execution and quality „made in Germany“
- For horizontal and vertical payout · payout left
- protection class IP 55
- technical details, dimension sheets and general terms and conditions see product brochure spring cable reels

Spring cable reel			
Article-No.	Horizontal payout	Vertical payout	Reel type
Coiling length in Meter			
4 x 1,5 mm², Ø 11,2 mm, 0,16 kg/m			
E1075-5000	7	7	LT155/108-4-26
E1076-5000	12	12	LT180/131-4-26
E1076-5005	27	18	LT180/231H4-26
E1077-5008	26	26	LT220/251H4-26
E1079-5011	47	35	LT300/252H4-26
5 x 1,5 mm², Ø 11,8 mm, 0,18 kg/m			
E1075-5001	7	7	LT155/108-5-26
E1076-5001	12	12	LT180/131-5-26
E1076-5006	20	18	LT180/231H5-26
E1077-5009	26	25	LT220/251H5-26
E1079-5012	47	31	LT300/252H5-26
7 x 1,5 mm², Ø 13,3 mm, 0,23 kg/m			
E1075-5002	7	7	LT155/108-7-26
E1076-5002	10	10	LT180/131-7-26
E1077-5002	12	12	LT220/151-7-26
E1077-5010	20	20	LT220/251H7-26
E1078-5002	26	24	LT221/251H7-26
E1079-5022	35	34	LT300/272H7-26
E1079-5013	49	24	LT300/252H7-26
12 x 1,5 mm², Ø 16,9 mm, 0,36 kg/m			
E1076-5003	7	7	LT180/131-12-26
E1077-5003	12	12	LT220/151-12-26
E1077-5011	22	15	LT220/251H12-26
E1078-5003	29	15	LT221/251H12-26
E1079-5004	22	22	LT300/252-12-26
E1079-5014	50	15	LT300/252H12-26

Spring cable reel			
Article-No.	Horizontal payout	Vertical payout	Reel type
Coiling length in Meter			
18 x 1,5 mm², Ø 17,9 mm, 0,47 kg/m			
E1077-5004	8	8	LT220/151-18-26
E1078-5004	18	12	LT221/251H18-26
E1079-5005	23	23	LT300/252-18-26
E1079-5024	29	21	LT300/272H18-26
E1081-5009	40	14	LT420/153-18-36
E1081-5006	73	14	LT420/283H18-36
24 x 1,5 mm², Ø 22,6 mm, 0,59 kg/m			
E1079-5000	14	9	LT300/152-24-36
E1079-5006	24	19	LT300/252-24-36
E1081-5011	41	22	LT420/253-24-36
30 x 1,5 mm², Ø 24,2 mm, 0,71 kg/m			
E1079-5001	12	8	LT300/152-30-36
E1079-5007	20	16	LT300/252-30-36
E1081-5012	38	20	LT420/253-30-36
4 x 2,5 mm², Ø 12,1 mm, 0,21 kg/m			
E1075-5000	7	7	LT155/108-4-26
E1076-5000	10	10	LT180/131-4-26
E1076-5005	18	16	LT180/231H4-26
E1077-5008	26	26	LT220/251H4-26
E1079-5011	46	27	LT300/252H4-26
5 x 2,5 mm², Ø 12,8 mm, 0,24 kg/m			
E1075-5001	7	7	LT155/108-5-26
E1076-5001	11	11	LT180/131-5-26
E1076-5006	18	14	LT180/231H5-26
E1077-5009	26	23	LT220/251H5-26
E1079-5012	46	23	LT300/252H5-26





Hartmann & König
STROMZUFÜHRUNGS AG

Spring cable reel

Article-No.	Horizontal payout	Vertical payout	Reel type
Coiling length in Meter			
7 x 2,5 mm², Ø 14 mm, 0,31 kg/m			
E1076-5002	10	10	LT180/131-7-26
E1077-5002	12	12	LT220/151-7-26
E1077-5010	17	17	LT220/251H7-26
E1078-5002	26	18	LT221/251H7-26
E1079-5013	47	18	LT300/252H7-26
E1079-5022	36	30	LT300/272H7-26
12 x 2,5 mm², Ø 20,2 mm, 0,48 kg/m			
E1077-5003	10	10	LT220/151-12-26
E1078-5003	16	12	LT221/251H12-26
E1079-5004	25	23	LT300/252-12-26
E1081-5008	41	15	LT420/153-12-36

Accessories

As part of our 48-hour-service we produce the most required accessories, like ratchet, roller yoke (fixed), and cable grip, on stock. They are ready for dispatch in combination with 48-hour cable reels.



Reel Type	Ratchet	Roller yoke
LT155	E2315-2000	E2350-2000
LT180	E2316-2000	E2351-2000
LT220	E2317-2000	E2352-2000
LT221	E2317-2000	E2353-2000
LT300	E2319-2000	E2354-2000
LT420	E2321-2000	E2356-2000
Cable diameter	Cable grip	
Ø 09 - 12 mm	X2850-0912	
Ø 12 - 15 mm	X2850-1215	
Ø 15 - 20 mm	X2850-1520	
Ø 20 - 25 mm	X2850-2025	
Ø 25 - 30 mm	X2850-2530	

Spring cable reel

Article-No.	Horizontal payout	Vertical payout	Reel type
Coiling length in Meter			
18 x 2,5 mm², Ø 20,6 mm, 0,68 kg/m			
E1077-5004	8	8	LT220/151-18-26
E1078-5004	15	8	LT221/251H18-26
E1079-5015	26	8	LT300/252H18-26
E1081-5001	34	20	LT420/283-18-36
24 x 2,5 mm², Ø 25,5 mm, 0,82 kg/m			
E1079-5017	12	11	LT300/172-24-36
E1079-5018	22	22	LT300/272-24-36
30 x 2,5 mm², Ø 28,7 mm, 0,97 kg/m			
E1081-5000	8	7	LT420/183-30-36
E1081-5003	20	14	LT420/283-30-36
4 x 4 mm², Ø 13,4 mm, 0,28 kg/m			
E1076-5004	10	10	LT180/131-4-40
E1077-5005	12	12	LT220/151-4-40
E1078-5005	26	20	LT221/251H4-40
E1079-5016	47	22	LT300/252H4-40
E1079-5025	35	34	LT300/272H4-40
4 x 6 mm², Ø 14,8 mm, 0,37 kg/m			
E1077-5006	12	12	LT220/151-4-60
E1077-5013	21	15	LT220/251H4-60
E1078-5006	26	15	LT221/251H4-60
E1079-5021	50	15	LT300/252H4-60
E1079-5026	36	25	LT300/272H4-60
E1081-5007	69	18	LT420/283H4-60
4 x 10 mm², Ø 18,8 mm, 0,61 kg/m			
E1077-5006	7	7	LT220/151-4-60
E1077-5007	13	13	LT220/251-4-60
E1078-5006	20	9	LT221/251H4-60
E1079-5026	29	15	LT300/272H4-60
E1081-5013	40	24	LT420/253-4-60
4 x 16 mm², Ø 23,4 mm, 0,92 kg/m			
E1079-5002	14	6	LT300/152-4-125
E1079-5010	20	12	LT300/252-4-125
E1079-5020	18	18	LT300/272-4-125
E1081-5005	25	14	LT420/283-4-150

CONCEIVE
CONNECT
CONDUCT

